

Water Technologies & Solutions

Sievers* M9 Turbo TOC Analyzers

Laboratory, Portable and On-Line



ready for the resource revolution



M9 Turbo... the next generation of Sievers TOC Analyzers

overview

With an analysis time of 4 seconds, a response time of 3.25 minutes, and an unprecedented analytical range of 0.20 parts per billion (ppb) to 10 parts per million (ppm) of total organic carbon (TOC), the Sievers M9 and M9^e Series Turbo TOC Analyzers provide the most accurate TOC data across the widest range, and provide it faster than any other TOC analyzer. Originally designed for optimizing water treatment systems, the Sievers M9 and M9^e Series of Turbo TOC Analyzers now are capable of fast analysis in grab sample or Autosampler mode.

applications

Microelectronics

For over a decade, the Sievers brand has provided the water reclaim industry with the only TOC analyzer that continuously and accurately measures TOC, even in the presence of interfering compounds such as Urea and TMAH (tetramethyl ammonium hydroxide). The Turbo membrane technology has been evaluated in two separate studies conducted by Sematech, a leading semiconductor research consortium, and recommended for the recycle role as a result of documented analytical performance¹. The Sievers M9 and M9^e Series Turbo TOC Analyzers offer an unparalleled combination of low-level sensitivity and high-level response while still improving analytical accuracy and precision.

Pharmaceutical

The M9 Series Turbo Analyzers are ideal for use in compendia testing, water system troubleshooting, and cleaning validation applications that require both fast and accurate TOC analysis. To support these applications, Sievers also offer an M9 Turbo Validation Support Package (VSP) that helps verify operational and performance parameters in Turbo mode.

Power

Power, chemical, and petrochemical companies rely on clean steam for optimal production. The Sievers M9 Turbo Analyzers allow for early and rapid leak detection of cooling fluids into condensate return to protect boiler water treatment equipment and the boiler itself from unwanted downtime and repairs.

Water System Diagnostics

M9 Turbo TOC Analyzers are the optimal solution for diagnosing water system problems. Because of their rapid analysis time, they can be useful in identifying periodic TOC spikes as well as other general water system TOC problems.

options and accessories

Turbo in the M9 Lab, Portable and On-Line Analyzer

The M9 Turbo is available across all three configurations of the instrument (laboratory, portable, on-line). The robust M9 On-Line Turbo is housed in a rugged IP-45 rated enclosure. The compact, lightweight M9 Portable Turbo is designed for maximum mobility in diagnostic applications, yet still capable of on-line measurements. Finally, the M9 Laboratory Turbo brings speed and accuracy to the benchtop.

Inorganic Carbon Remover (ICR)

The integrated Inorganic Carbon Remover (ICR*) reduces inorganic carbon levels in sample streams with high IC/TOC ratios to produce more accurate TOC results.

Sample Conductivity

Measure and report sample conductivity for pharmaceutical applications in discrete grab samples.

system specifications

operating specifications²

Range	0.20 ppb to 10 ppm
Precision	2% RSD
Accuracy	± 10% or ±10 ppb whichever is greater
Display Readout	3 significant digits
Calibration	Typically stable for 12 months
Analysis Time	4 seconds
Response Time	3.25 Minutes
Sample Temperature ³	5–95° C (41–203° F) – withstands short-term steam exposure
Ambient Temperature	10–40° C (50–104° F)
Sample Pressure ³	Up to 100 psi (online and portable)
Instrument Sample Flow Rate	1.1 mL/min

analyzer specifications

laboratory

on-line

portable

	laboratory	on-line	portable
Outputs	USB device port (1), USB host ports (3); Modbus TCP/IP	4-20 mA outputs (3); alarm outputs (4); binary i input (1); USB device port (1), USB host ports (2); Modbus TCP/IP	
Display	7" WVGA 800x480 pixel, Color LCD w/touch-screen		
Power	100 – 240 V~, 50 – 60 Hz, 100 VA		
Fuses	Replace with same type and size fuse: T 1.6 A 350 VAC Fuse (Slow Blow), size 5 x 20 mm appliance inlet		
Dimensions	H: 42.2 cm (16.6 in.) W: 24.6 cm (9.7 in); D: 40.0 cm (15.8 in)	H: 54.9 cm (21.6 in); W: 45.0 cm (17.7 in); D: 26.5 cm (10.4 in)	H: 39.5 cm (15.4); W: 22.9 cm (9.0 in); D: 46.4 cm (18.3 in)
Weight	9.4 kg (20.6 lb)	15.8 kg (34.9 lb)	9.4 kg (20.8 lb)
Enclosure Rating	n/a	IP-45	IP-21
Safety Certifications	ETL. CE		

consumables

UV Lamp	6 months
Acid Reagent	As needed, typically for 3 months (285 mL)
Oxidizer Reagent	As needed, typically 3-month stability; available in 150- or 300-mL cartridge



References

1. *Ultrapure Water*, February 1999 and March 1999.
2. Stated analytical performance is achievable under controlled laboratory conditions that minimize operator and standards errors.
3. If the sample temperature is above 60° C (140° F), an optional PVDF iOS is required.

 The UV lamp inside this product contains mercury and must be recycled or disposed of in accordance with local, state, and federal laws.

This information herein may be subject to change without notice and is provided for general guidance only. The dimensions and performance of systems, products and services may vary. Pictures are for example purposes and not to scale. All legal obligations are exclusively as set out in contractual documents. Nothing contained herein constitutes a representation, warranty or undertaking.



6060 Spine Road
Boulder, CO 80301-3687 USA
T +1 800 255 6964
T +1 303 444 2009
F +1 303 527 1797
www.sieversinstruments.com



Find a contact near you by visiting www.sieversinstruments.com and clicking on "Contact Us".

* Trademark of SUEZ; may be registered in one or more countries.

2017 © Copyright SUEZ. All rights reserved.