

DCT 532



Industrial Pressure Transmitter with i²C interface

Stainless Steel Sensor

Accuracy according to IEC 60770:
≤ ± 0.25 % FSO

Nominal pressure

from 0 ... 100 mbar up to 0 ... 400 bar

Digital output signal

- i²C
- bus frequency max. 400 kHz
- configuration of data format
- interrupt signal

Special characteristic

- ▶ perfect thermal behaviour
- ▶ excellent long term stability

Optional versions

- ▶ pressure port
G 1/2" flush up to 40 bar
- ▶ welded sensor
- ▶ customer specific versions

Contrary to the industrial pressure transmitter with analogue signal, the DCT 532 has a digital i²C-interface. i²C has a master-slave topology, whereby you can use up to 127 devices at one master. In addition to the typical settings, as slave address, data format, etc., it is possible to do special parametrisation for pressure unit and more.

Due to the usage of high quality materials and components, the DCT 532 is suitable for almost every industrial application, if medium is compatible with stainless steel 316L.

The modular concept of the pressure transmitter allows customized electrical or mechanical connections, so it is easy to adapt the pressure transmitter to different conditions on-site.

Preferred areas of use are



Plant and machine engineering



Energy industry



Input pressure range												
Nominal pressure gauge	[bar]	-1...0	0.10	0.16	0.25	0.40	0.60	1	1.6	2.5	4	6
Nominal pressure abs.	[bar]	-	-	-	-	0.40	0.60	1	1.6	2.5	4	6
Overpressure	[bar]	5	0,5	1	1	2	5	5	10	10	20	40
Burst pressure ≥	[bar]	7.5	1.5	1.5	1.5	3	7.5	7.5	15	15	25	50

Nominal pressure gauge / abs.	[bar]	10	16	25	40	60	100	160	250	400
Overpressure	[bar]	40	80	80	105	210	600	600	1000	1000
Burst pressure ≥	[bar]	50	120	120	210	420	1000	1000	1250	1250
Vacuum resistance		$p_N \geq 1$ bar: unlimited vacuum resistance $p_N < 1$ bar: on request								

Output signal / Supply	
i ² C	$V_S = 3.5 \dots 5.5 V_{DC}$

Performance	
Accuracy ¹	$\leq \pm 0.25$ % FSO
Max. I/O current	10 mA
Long term stability	$\leq \pm 0.1$ % FSO / year at reference conditions
Response time	1.5 msec + transmission time (depending on bus frequency)
Measuring rate	500 Hz

¹ accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)

Thermal effects (offset and span)	
Tolerance band	$\leq \pm 0.75$ % FSO
in compensated range	-20 ... 85 °C

Permissible temperatures	
Medium	-25 ... 125 °C
Electronics / environment	-25 ... 85 °C
Storage	-40 ... 85 °C

Electrical protection	
Short-circuit protection	permanent
Reverse polarity protection	by exchanged supply connections no damage, but also no function by exchanged communication with signal lines it can come according to constellation to damages.
Electromagnetic compatibility	emission and immunity according to EN 61326

Mechanical stability	
Vibration	10 g RMS (25 ... 2000 Hz) according to DIN EN 60068-2-6
Shock	500 g / 1 msec according to DIN EN 60068-2-27

Materials	
Pressure port / Housing	stainless steel 1.4404 (316 L)
Seals (media wetted)	standard: FKM options: EPDM welded version ² (for $p_N \leq 40$ bar) others on request
Diaphragm	stainless steel 1.4435 (316 L)
Media wetted parts	pressure port, seal, diaphragm

² welded version only with pressure ports according to EN 837, $p_N \leq 40$ bar

Miscellaneous	
Current consumption	< 15 mA
Weight	approx. 140 g
Ingress protection	IP 67
Installation position	any ³
Operational life	100 million load cycles
CE-conformity	EMC Directive: 2014/30/EU Pressure Equipment Directive: 2014/68/EU (module A) ⁴

³ Pressure transmitters are calibrated in a vertical position with the pressure connection down. If this position is changed on installation there can be slight deviations in the zero point for pressure ranges $p_N \leq 1$ bar.

⁴ This directive is only valid for devices with maximum permissible overpressure > 200 bar

Wiring diagrams		
Pin configuration		
Electrical connection	M12x1 / metal (5-pin)	Binder 723 (5-pin)
Supply +	1	1
Supply -	3	3
SDA	2	2
SCL	4	4
INT	5	5
Shield	housing	housing
Electrical connections (dimensions mm / in)		
standard	optionally	
M12x1 (5-pin)	Binder Serie 723 (5-pin)	

Ordering code DCT 532

DCT 532



Pressure										
	gauge		D	C	0					
	absolute	¹	D	C	1					
Input										
	[bar]									
	0.10	¹			1	0	0	0		
	0.16	¹			1	6	0	0		
	0.25	¹			2	5	0	0		
	0.40				4	0	0	0		
	0.60				6	0	0	0		
	1.0				1	0	0	1		
	1.6				1	6	0	1		
	2.5				2	5	0	1		
	4.0				4	0	0	1		
	6.0				6	0	0	1		
	10				1	0	0	2		
	16				1	6	0	2		
	25				2	5	0	2		
	40				4	0	0	2		
	60				6	0	0	2		
	100				1	0	0	3		
	160				1	6	0	3		
	250				2	5	0	3		
	400				4	0	0	3		
	-1 ... 0		X		1	0	0	2		
	customer				9	9	9	9		consult
Output										
	°C								IC	
Accuracy										
	0.25 % FSO								2	
	customer								9	consult
Electrical connection										
	male plug M12x1 (5-pin) / metal					N	1	7		
	male plug Binder series 723 (5-pin)					2	0	7		
	customer					9	9	9		consult
Mechanical connection										
	G1/2" DIN 3852						1	0	0	
	G1/2" EN 837						2	0	0	
	G1/4" DIN 3852						3	0	0	
	G1/4" EN 837						4	0	0	
	G1/2" DIN 3852 with flush sensor ²						F	0	0	
	G1/2" DIN 3852 open pressure port ²						H	0	0	
	1/2" NPT						N	0	0	
	1/4" NPT						N	4	0	
	customer						9	9	9	consult
Seals										
	FKM								1	
	EPDM								3	
	without (welded version) ³								2	
	customer								9	consult
Special version										
	standard								0	0
	customer								9	9
										9
										consult

¹ absolute pressure possible from 0.4 bar

² not possible for nominal pressure $p_N > 40$ bar

³ welded version only with pressure ports according to EN 837, possible for $p_N \leq 40$ bar