Additel 901B Low Pressure Test Pump

- Generate 6 psi (0.4 bar) vacuum to 6 psi (0.4 bar) pressure
- Portable, only 3.5 lb
- Great stability and high resolution
- Minimal maintenance
- Hand-tight quick connectors

OVERVIEW

The 901B Low Pressure Test Pump is a hand operated pressure pump designed to generate pressures from -6 psi (-0.4 bar) to 6 psi (0.4 bar). A high-quality screw press is designed for fine pressure adjustment, with an adjustment resolution up to 0.1 Pa (0.001 mbar). The 901B is a very stable low pressure calibrator. It makes use of an isothermal bellows chamber which is designed for reducing the possible effects of environmental temperature change. Most pumps make use of a check valve (non-returning valve) and are not well insulated which will cause large fluctuations in pressure with a change in ambient temperature or when the unit is touched. The 901B does not use a check valve and is remarkably stable. Two hand-tight connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The 901B is an ideal comparison test pump for low pressure applications.

SPECIFICATIONS

Generated Pressure Range

Ram/adapters: SS

Body: SS, aluminum

female, or M20X1.5 female

Weight: 3.5 lb (1.6 kg).

Warranty: 1 year.

Dimensions: Height: 5.7" (145mm)

Media: Air.

Material:

Connection

gauge.

FEATURES

- Portable: Only 3.5 lb (1.6 kg)
- Adjustment Resolution

0.1Pa (0.001 mbar); Specially designed screw press for fine pressure adjustment.

Great Stability

Isothermal chamber: the pressure chamber is insulated to reduce the influence from environmental temperature changes.

Specially designed bellows minimize leakage to guarantee excellent stability.

- Durable and Minimal Maintenance Without non-returning valve that is usually used on troublesome hand pump.
- Easy-to-use

Manual: 1 pc

Pressure could be set and adjusted precisely and quickly through a simple turn of the handle.

Hand-tight Quick Connectors Allows easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches.

ORDERING INFORMATION



	Model Number				
		0T901B — N • • SET	Model number	Description	
			ADT901B-X-kit	Test kit for ADT901B (barb fitting, connection hoses, and adapters). X=connection type e.g. N-1/4NPTM, N2-1/2NPTM, B-1/4BSPM, B2-1/2BSPM, M-M20X1.5M.	
	Model			Adapters and fittings, 1/4NPT male to various male and female connection (25 pcs). More information shown on page 69	
	Pressure port type: N -1/4NPT female	included	ADT103	Adapters and fittings, 1/4NPT (1/2NPT, 1/4BSP, 1/2BSP, or M20X1.5) male to various female hand-tight quick connectors (10 pcs). More information shown on page 70	
	N2 - 1/2NPT female B - 1/4BSP female		9901-901	Carrying Case for one ADT901B pump and two ADT681 gauges or ADT672 calibrators	
	B2 - 1/2BSP female		ADT901B-MK	Maintenance kit for Additel 901B pump	
M-M20X1.5	M-M20X1.5 female		9240	Differential pressure gauge holder	
	Accessories included O-ring: 20 pcs		Note: For oil free	e applications contact Additel.	

Phone: 714-998-6899 Fax: 714-998-6999 Email: sales@additel.com Rev # 20200629

Carrying case (901B-X-SETmodels only)

Corporate Headquarters 2900 Saturn St #B Brea, CA 92821, USA

Salt Lake City Office 1364 West State Rd. Suite 101 Pleasant Grove, UT 84062, USA

Metrology Made Simple



6 psi (0.4 bar) vacuum to 6 psi (0.4 bar) positive pressure.

Hand-tight connectors for both test gauge and reference

1/4NPT female, 1/2NPT female, 1/4BSP female, 1/2BSP

Base: 9.65" (245 mm) x 6.50" (165mm)

Adjustment Resolution: 0.1 Pa (0.001 mbar).

Seals: Buna-N, PTFE, Copper Allov



01